

AUWELD ARC- 400V2 Welding Machine 3PH/415V

Description

The *ARC 400V2* offers more than you would expect from a welder this size. It packs the full punch of a heavyweight professional that you can take to the most demanding job sites. It's using advanced inverter technology to transfer 50/60Hz power frequency electric.

Specification

Madal	
Model	ARC 400V2
Welding Process	MMA (SMAW)
	LIFT TIG
Input Power Voltage (V)	Three Phase
	AC 415V±10% (50/60 Hz)
Rated Input Power Capacity (kVA)	18.2
Output Current Voltage (A)	20 - 400
No-Load Voltage (V)	67
Duty Cycle (%)	60
Arc Force	20 – 150
Diameter of Rod	2.5 - 5.0
Efficiency (%)	85

Model Power Factor (%)	ARC 400V2
Insulation Class	F
Protection Class	IP21S
Weight (kg)	24
Dimension (mm)	515 x 280 x 435
Industrial Application	Shipyard, Oil & Gas

Features

- Microprocessor control; simple operation, more perfect welding performance.
- Provides quick, direct connection to remote controls and switches.
- The unique air design; failure rate greatly reduced, extending the service life of the machine.
- Suitable for all types of electrodes including cellulosic.

Include Items

- 1 pc Electrode Holder (2.5m)
- 1 pc Earth Clamp (2.5m)