

AUWELD ARC- 500V2 Welding Machine 3PH/415V

Description

The *ARC 500V2* offers more than you would expect from a welder this size. It packs the full punch of a heavyweight professional that you can take to the most demanding job sites. It's using advanced inverter technology to transfer 50/60Hz power frequency electric.

Specification

Model	ARC 500V2
Welding Process	MMA (SMAW)
	LIFT TIG
Input Power Voltage (V)	Three Phase
	AC 415V±10% (50/60 Hz)
Rated Input Power Capacity (kVA)	25.3
Output Current Voltage (A)	20 – 500
No-Load Voltage (V)	67.5
Duty Cycle (%)	60
Adjustment Range (10A/1)	0 - 20
Efficiency (%)	85
Power Factor (%)	0.93

Model Insulation Class	ARC 500V2
Protection Class	IP21S
Weight (kg)	24.5
Dimension (mm)	500 x 280 x 435
industrial Application	Shipyard, Oli & Gas

Features

- Characteristics: High efficiency, compact, low energy consumption, and good dynamic, stable arc, continuous adjustable current and more
- **Protective Function**: Protection for over voltage, over current, over heat to ensure safety and durability
- Various Welding Materials: Acidic basic and cellulose rod which are used for stainless steel, alloy steel, carbon steel, copper and other nonferrous metal welding
- Advantage compared to other: Easy installation and operation

Include Items

- 1 pc Electrode Holder (2.5m)
- 1 pc Earth Clamp (2.5m)