



EVERSAFE ABC Powder Fire Extinguisher 2KG

Description

Features

- Fully deep drawn from cold rolled steel
- Effective on all types of fires – Class A, B, C and electrical fires
- Effective heat shield greatly reduces heat from fire
- Immediate knockdown of flames
- Rigid quality controlled dry chemical powder
- Economical investment for fire protection

Specification

Model	EC-2
Type	Stored Pressure Type
Extinguishant	ABC Dry Powder
Capacity	2 kg
Propellant	Nitrogen (N ²)
Valve	Controllable Non Ferrous Valve with Pressure Indicator
Body Diameter (mm)	110
Overall Height (mm)	370
Approx. Full Weight	3.3 kg
Working Temperature Range	-20°C to + 60°C
Working Pressure	12 bar
Test Pressure	25 bar
Burst Pressure	Exceeds 69 bar

Model	EC-2
Approx. Discharge Range (m)	2m – 4m
Approx. Discharge Time (sec)	12
Fire Rating (Min)	8A:34B
Fire Class	ABC + Electrical
Internal Coating	Stoving Epoxy Primer
Paint Finishing	RAL 3000 Flame Red Epoxy Polyester Powder Coating
Mounting	Plastic Bracket
Manufactured & Certified to	MS 1539 : Part 1 : 2002