

EVERSAFE ABC Powder Fire Extinguisher 6KG

Description

Features

- Fully deep drawn from cold rolled steel
- Effective on all types of fires Class A, B, C and electrical fires
- Effective heat shield greatly reduces heat from fire
- Immediate knockdown of flames
- · Rigid quality controlled dry chemical powder
- Economical investment for fire protection

Specification

Model	EC-6
Туре	Stored Pressure Type
Extinguishant	ABC Dry Powder
Capacity	6 kg
Propellant	Nitrogen (N ²)
Valve	Controllable Non Ferrous Valve with Pressure Indicator
Body Diameter (mm)	158
Overall Height (mm)	525
Approx. Full Weight	9.3
Working Temperature Range	-20°C to + 60°C
Working Pressure	12 bar
Test Pressure	25 bar
Burst Pressure	Exceed 69 bar

Model	EC-6
Approx. Discharge Range (m)	6 m – 7 m
Approx. Discharge Time (sec)	17
Fire Rating (Min)	27A:144B
Fire Class Internal Coating	ABC + Electrical Stoving Epoxy Primer
Paint Finishing Mounting	RAL 3000 Flame Red Epoxy Polyester Powder Coating Metal 'L' Wall Bracket
Manufactured & Certified to	MS 1539: Part 1 : 2002